

Assessment of Performance Report n.1880-AoP-064-25

For the purposes of Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction products Regulation or CPR), this Assessment of Performance Report under AVCP system 3 applies to the construction products

Brand - Models:

AGE STUFE - Clara 14 s
AGE STUFE - Clara 14 s Canalizzata
AGE STUFE - Vanity 14 s
AGE STUFE - Vanity 14 s Canalizzata
AGE STUFE - Aliscia 14 s
AGE STUFE - Aliscia 14 s Canalizzata
AGE STUFE - Megan 14 s
AGE STUFE - Megan 14 s Canalizzata
AGE STUFE - Kate 14 s
AGE STUFE - Kate 14 s Canalizzata
MHAUSER - Lara 15
MHAUSER - Lara 15 Canalizzata
MHAUSER - Diadema 15
MHAUSER - Diadema 15 Canalizzata
MHAUSER - Giusy 15
MHAUSER - Giusy 15 Canalizzata
mechanically by wood pellets fed roomheater without boiler
placed on the market under the name or trademark of
AGE STUFE SRL
VIA DELL'ARTIGIANATO 574
37040 ZIMELLA (VR)

This Assessment of Performance Report attests that the performance of the above-mentioned construction product has been assessed in accordance with the harmonized standard

EN 16510-2-6:2022

under AVCP system 3 with regard to the essential characteristics listed in Annex 1.

Basis of the assessment: testing and issuing of Test report 1880-CPR-064-25.

This Assessment of Performance Report has been drawn up in accordance with the GNB Position Paper NB-CPR 23/836 and covers only the essential characteristics listed in Annex 1. It is not an exhaustive statement of the performance of the product. The manufacturer is responsible for the Declaration of Performance of the product and can declare the performance of other essential characteristics than those mentioned in Annex 1.

This Assessment of Performance report is not considered a product certificate or a document to directly accompany neither the product nor the Declaration of Performance. See CPR Article 4(3).

This Assessment of Performance Report will remain applicable, under the manufacturer's responsibility, as long as neither the harmonised standard, the construction product, nor the AVCP methods are modified significantly.

November 19, 2025

Head of laboratory
dr.ssa Claudia Marcuzzi

Firmato
digitalmente da
MARCUIZZI CLAUDIA
Data: 2025.11.19
14:29:04 +01'00'

ANNEX 1

Essential characteristic	Performance	Basis for the assessment of performance
Mechanical resistance and stability		
Load bearing capacity	0 kg	declared by the manufacturer
Safety in case of fire		
Protection of combustible materials Minimum distance to combustible materials	bottom d _B 3 cm floor in front d _F 150 cm ceiling d _C -- cm rear d _R 20 cm side d _S 20cm side radiation d _L 150 cm front d _P 200 cm	Test report n. 1880-CPR-064TR-25
Protection of combustible materials Thickness - type of protective insulation	— _d	
Hygiene, health and the environment		
Emission of combustion products [ref. at 13% O ₂]:	at nominal – part load heat output: CO 78 – 292 mg/m ³ NO _x 96 – 103 mg/m ³ OGC 1 – 6 mg/m ³ PM 10 – 5 mg/m ³	Test report n. 1880-CPR-064TR-25
Safety and accessibility in use		
Data for installation to a chimney at nominal – part load heat output:		
Flue gas outlet temperature	141 – 81,6°C	Test report n. 1880-CPR-064TR-25
Minimum flue draught	10,5 – 10,0 Pa	
Flue gas mass flow	8,0 – 5,8 g/s	
Data for installation to a chimney regarding fire safety on safety test heat output:		
Fire safety of installation to a chimney	T200	declared by the manufacturer
Energy economy and heat retention		
Appliance's thermal output and energy efficiency at nominal – part load heat output:		
Space heat output	12,4– 4,9 kW	Test report n. 1880-CPR-064TR-25
Efficiency	92,6 – 93,2 %	
Space heating efficiency		
Seasonal space heating efficiency at appliance's nominal heat output	89,3 %	Test report n. 1880-CPR-064TR-25
Energy efficiency	EEI 131	
	class A++	
Electric power consumption at appliance's nominal heat output	130 W	
Electric power consumption at appliance's part load heat output	45 W	
Standby mode power consumption	3 W	
Sustainable use of natural resources		
Environmental sustainability	NPD	declared by the manufacturer